Safety Data Sheet

Issue Date: 01-Jan-2007 Revision Date: 09-Mar-2015 Version 1

1. IDENTIFICATION

Product Identifier

Product Name Acrylic Sealer

Other means of identification

SDS # DYNI-005

Recommended use of the chemical and restrictions on use

Recommended Use Floor Sealer.

Details of the supplier of the safety data sheet

Supplier Address

Clean Cut 16 Meredith Circle

Needham, MA 02492

Emergency Telephone Number

Company Phone Number Phone: 781-352-4707

Fax: 781-352-4708

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear or translucent liquid Physical State Liquid Odor Mild

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

Other Hazards

Harmful to aquatic life with long lasting effects Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
tributoxyethyl phosphate	78-51-3	1-5
Zinc Oxide	1314-13-2	<1
Ammonium hydroxide	1336-21-6	<1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment. If exposed or concerned: Get medical

advice/attention.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

Symptoms Ingestion may cause nausea. Direct contact may cause skin or eye irritation. Prolonged

exposure may produce headaches and mucous membrane irritation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Hazardous Combustion Products Toxic gases may be released.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsUse personal protective equipment as required.

Environmental Precautions See Section 12 for additional Ecological Information. Prevent entry into drains, sewers and

other waterways.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Absorb with inert material, and then place in suitable container for chemical waste.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. For industrial or

professional use only. Keep away from heat/sparks/open flames/hot surfaces. — No

smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep

storage temperature between 4-32 °C (40-90 °F).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Zinc Oxide	STEL: 10 mg/m ³ respirable	TWA: 5 mg/m ³ fume	IDLH: 500 mg/m ³
1314-13-2	fraction	TWA: 15 mg/m ³ total dust	Ceiling: 15 mg/m ³ dust
	TWA: 2 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m ³ dust and fume
		(vacated) TWA: 5 mg/m ³ fume	STEL: 10 mg/m ³ fume
		(vacated) TWA: 10 mg/m ³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
		(vacated) STEL: 10 mg/m ³ fume	

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Showers.

Eyewash stations. Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety goggles are recommended.

Skin and Body Protection Rubber gloves recommended.

Respiratory Protection Respiratory protection is recommended where exposure limits are exceeded.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid

Appearance Clear or translucent liquid Odor Mild

Color Clear or translucent Odor Threshold Not determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH 7.0-9.5 Melting Point/Freezing Point Variable

Boiling Point/Boiling Range 100 °C / 212 °F **Flash Point** > 121 °C / 250 °F

Evaporation Rate 1 (Water = 1)

Flammability (Solid, Gas)
Upper Flammability Limits
Lower Flammability Limit
Vapor Pressure

Liquid-Not Applicable
Not determined
Not determined
Not determined

Vapor Density 1 (Water Vapor=1)

Specific Gravity Variable

Water Solubility Infinitely miscible Solubility in other solvents Not determined

Property Values Remarks • Method

Partition Coefficient
Auto-ignition Temperature
Decomposition Temperature
Kinematic Viscosity
Dynamic Viscosity
Explosive Properties
Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures of 212°F or above will boil water away.

Incompatible Materials

Materials incompatible with water.

Hazardous Decomposition Products

Thermal decomposition may produce toxic vapor or gas.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact May cause eye irritation on direct contact.

Skin Contact Direct contact may cause skin irritation.

Inhalation Prolonged exposure may produce headaches and mucous membrane irritation.

Ingestion Nausea may occur.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Di(ethylene glycol) ethyl ether 111-90-0	= 1920 mg/kg (Rat)	= 4200 μ L/kg (Rabbit) = 6 mL/kg (Rat)	> 5240 mg/m³ (Rat) 4 h
tributoxyethyl phosphate 78-51-3	= 3000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 6.4 mg/L (Rat)4 h
Zinc Oxide 1314-13-2	> 5000 mg/kg(Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-
Propylene Glycol Phenyl Ether 770-35-4	= 2830 mg/kg(Rat)	> 2 g/kg(Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

Based on the information provided, this product does not contain any carcinogens or

potential carcinogens as listed by OSHA, IARC or NTP.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Di(ethylene glycol) ethyl		11400 - 15700: 96 h		3940 - 4670: 48 h Daphnia
ether		Oncorhynchus mykiss mg/L		magna mg/L EC50
111-90-0		LC50 flow-through 11600 -		
		16700: 96 h Pimephales		
		promelas mg/L LC50 flow-		
		through 10000: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static 19100 - 23900:		
		96 h Lepomis macrochirus		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
tributoxyethyl phosphate		10.4 - 12.0: 96 h Pimephales		
78-51-3		promelas mg/L LC50 flow-		
		through		
Ammonium hydroxide		8.2: 96 h Pimephales		0.66: 48 h water flea mg/L
1336-21-6		promelas mg/L LC50		EC50 0.66: 48 h Daphnia
				pulex mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Di(ethylene glycol) ethyl ether 111-90-0	-0.8
tributoxyethyl phosphate 78-51-3	4.78

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Zinc Oxide	Toxic
1314-13-2	
Ammonium hydroxide	Toxic
1336-21-6	Corrosive

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

<u>IATA</u> Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
tributoxyethyl phosphate	Present	Х		Present		Present	X	Present	Х	X
Zinc Oxide	Present	Х		Present		Present	Х	Present	Х	Х
Ammonium hydroxide	Present	Х		Present		Present	Х	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ammonium hydroxide	1000 lb		RQ 1000 lb final RQ
1336-21-6			RQ 454 kg final RQ

-

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Di(ethylene glycol) ethyl ether - 111-90-0	111-90-0	5-10	1.0
Zinc Oxide - 1314-13-2	1314-13-2	<1	1.0
Ammonium hydroxide - 1336-21-6	1336-21-6	<1	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc Oxide		X		
Ammonium hydroxide	1000 lb			X

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Di(ethylene glycol) ethyl ether 111-90-0	X		X
Zinc Oxide 1314-13-2	X	X	X
Ammonium hydroxide 1336-21-6	Х	Х	X

16. OTHER INFORMATION

NFPAHealth HazardsFlammabilityInstabilitySpecial Hazards100Not determinedHMISHealth HazardsFlammabilityPhysical HazardsPersonal ProtectionNot determinedNot determinedNot determinedNot determined

Issue Date:01-Jan-2007Revision Date:09-Mar-2015Revision Note:New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet